

Renegade Pullers of Minnesota

General Rules

- Drivers must be at least 18 years of age or older.
- Driver must be present at drivers meeting.
- May be 200 lbs. max over the posted class weight.
- No tires chains, pressurized fuels, nitrous oxide or oxidizing agents.
- All engine radiator fans must be properly shrouded. All clutches, pressure plates, fly wheels, and drive train components must have 360 degree shroud of 3/16" or greater metal material.
- Minimum drawbar length 18 inches from center of rear axle to point of hook, and may not pull from two or three point hitching mechanisms.
- Drawbar is to be stationary in all directions and not to exceed 20" to top of drawbar.
- All weights must be safely secured to the tractor and rear weights cannot interfere with hooking and unhooking to the sled.
- If anything falls off during the pull, you will be disqualified.
- All tractors must weight immediately before lining up with driver on the seat.
- Puller must operate in a safe manner at all times and stay seated and have ne hand on the steering wheel.
- Must be in neutral when hooking and unhooking from the sled.
- All pulls start with a tight chain – no jerking.
- Driver will be allowed ONE restart if stopped before 100'.
- Driver must stop immediately upon signal from the judge, the pull is over when forward motion stops.



Renegade Pullers of Minnesota 410 Rules

410 Class 9500 lbs. Improved Stock

- Stock appearing engine & sheet metal, transmission, and rear end must match brand.
- Must have factory built wide front steer axle from any brand (tractor), No combine steering axles
- No truck parts allowed. Must use all Ag parts. 410 cubic inch max. Engine block must be from a 410 cubic inch or smaller. Mandatory cubic inch check prior to the season starting if you plan on participating in the class for points. \$100.00 Tech Fee.
- Stock appearing carburetors & rotary fuel injection pumps. No inline fuel injection pumps allowed in this class.
- One fuel only diesel or gas, No pressurized fuels, nitrous oxide or other oxidizing agents allowed.
- A Single T4 flange turbocharger is allowed with up to a 2.25 inch max intake. Turbo inlet vanes must protrude 1/8" into the max 2.25" intake bore. (No slots or slugs allowed)
- Exhaust must be cross bolted after turbo.
- Cross over pipe max length 40" and max diameter 3.78".
- No water injection of any kind. No inner coolers.
- No speed or RPM limit.
- 18.4 x 38 max tire size. No V, single, or double cut tires.
- No weight can extend 24" beyond the furthest most stock point of the front end of the tractor.
- **ALLOWED:** Pulling hitch, Weld on hubs, steel wheels, Radial tires, Aluminum front wheels, & weight brackets.
- **NOT ALLOWED:** Duals, curved exhaust pipes, Aluminum frame / chassis.
- Tractor must have wheelie bars
- Over 3000 RPM must have the following safety equipment: Steel flywheel and necessary shields for rotating components
- Base of seat, ROPS, and roll cages must be properly secured to the tractor
- Helmet and seatbelt are required if tractor is equipped with a roll cage or narrow ROPS
- No helmet required if equipped with a factory width ROPS.
- Fire extinguisher recommended and mounted for easy accessibility.