

Renegade Pullers of Minnesota

General Rules

- Drivers must be at least 18 years of age or older.
- Driver must be present at drivers meeting.
- May be 200 lbs. max over the posted class weight.
- No tires chains, pressurized fuels, nitrous oxide or oxidizing agents.
- All engine radiator fans must be properly shrouded. All clutches, pressure plates, fly wheels, and drive train components must have 360 degree shroud of 3/16" or greater metal material.
- Minimum drawbar length 18 inches from center of rear axle to point of hook, and may not pull from two or three point hitching mechanisms.
- Drawbar is to be stationary in all directions and not to exceed 20" to top of drawbar.
- All weights must be safely secured to the tractor and rear weights cannot interfere with hooking and unhooking to the sled.
- If anything falls off during the pull, you will be disqualified.
- All tractors must weight immediately before lining up with driver on the seat.
- Puller must operate in a safe manner at all times and stay seated and have ne hand on the steering wheel.
- Must be in neutral when hooking and unhooking from the sled.
- All pulls start with a tight chain – no jerking.
- Driver will be allowed ONE restart if stopped before 100'.
- Driver must stop immediately upon signal from the judge, the pull is over when forward motion stops.



Renegade Pullers of Minnesota 466 Rules

466 Class 11,000 lbs. Hot Farm

- Stock appearing block, driveline, transmission, front and rear axle, and sheet metal must match model of the manufacturer.
- After market nose piece and hoods allowed.
- No intercoolers or aftercoolers allowed.
- 466 cubic inch or smaller engine only, with OEM Ag head and manifolds. (No truck manifolds allowed)
- Stock appearing fuel injection pump, NO P-pumps allowed.
- No spacer blocks – between the block and the cylinder head or between the block and the intake manifold.
- One turbo only – with a max inlet of 2.8" and outlet size of 3". No slots or slugs. No waste gate or variable turbo. Intake wheel must protrude 1/8" into housing.
- Max tire size, 20.8x38
- Lubrication allowed in water injection, but no additives.
- No speed limit or rpm limit
- One fuel only, Diesel or Gas, no pressurized fuels, nitrous oxide or other oxidizing agents allowed.
- **ALLOWED:** Pulling hitch, water injection, pusher pump, weld on hubs, steel wheels, aluminum front wheels and weight brackets.
- **NOT ALLOWED:** V or double cut pulling tires, aluminum frame/chassis, curved exhaust pipes.

Mandatory Safety Equipment in ALL Hot Farm Classes:

- Steel Flywheel
- Air Shut off – needs to disconnect and the rear of the tractor and hook to the sled
- Side Shields (recommended to follow NTPA rules)
- ROPS with seatbelt, Cages allowed. Helmets recommended and required in all tractors with a cage.
- Wheelie bars, Fenders, Fire Extinguisher and Wide Front
- Drivers must wear long pants (no shorts)
- Any type of safety equipment is recommended