

## **Full Throttle Promotions Stock Minivan, Mini Truck, and SUV 2022 Rules**

\*\*\*If the vehicle does not pass inspection or driver is unwilling to change the vehicle to pass inspection - absolutely no refunds!!

1. Ages 14 –17 must have a notarized permission slip.
2. DO NOT hit the driver's door! Sometimes this happens, but if it looks intentional or carelessness, you will be disqualified. Don't use your door as a shield; it may cause you to get disqualified.
3. NO sandbagging or holding!!! You will be disqualified!!!
4. You are given 20 seconds for aggressive hits, 1 minute for restarts and 1 minute if you are hung up.
5. Vehicles are subject to re-inspection before any prize money is handed out.
6. All vans must be stock unless modification is stated in the rules.
7. All glass, plastic, chrome, and interior must be removed from the van before arriving to the derby.
8. You must have a visible roof sign with car number on it
9. Driver must have a long sleeve or non-flammable jacket, pants, closed toe shoes to wear while driving in the event.
10. If you are running an electric fuel pump – it must be hooked up to your ignition switch – so when your car shuts off – it shuts off.

### **(Front and Rear Wheel Drive Vans) (Example: Caravan, Astro, Aerostar)**

### **Minitruck/suv-open to gm s-10, ford ranger, dodge Dakota pickups, ford explorers, gm blazers, 98-03 dodge Durango.**

11. Vehicle must remain completely stock. This is meant to be a quick build class with no modification or swapping of parts.
12. No welding allowed except driver's door and differentials.
13. Must add a seat support bar and dash bar inside the vehicle post to post. Inside door bars attached only to the dash, the seat bar on driver's side and passenger side must be within 6 inches of the seat.
14. No torching the fenders. Vehicle must be totally stock appearing.
15. 12" Fire hole in hood required.
16. No pre-bending of body panels.
17. Can relocate electrical boxes.
18. Remove gas tank and mount a steel tank inside the center of the vehicle, securely fastened down and covered. Battery must be moved inside of the vehicle and securely mounted away from any door and covered. Must be high pressure fuel line. Must be safe or will not run.
19. Two chains per vertical door seam. No chains on the bottom or top of the doors. Four chains per hood. Rear hatch and doors 4 total hold downs max. No reinforcement.
20. All suspension and struts must be stock. NO strut clamps or spacers. 2 leaf spring clamps total, per spring. No chaining of suspension.



21. Automotive DOT 6 Ply tires max allowed. No skid loader, industrial, implement, or trailer tires allowed. Snow tires and donut spares can be used. Air inflated only. Valve stem protectors allowed, must be flush to the rim.
22. All airbags must be removed and disabled.
23. Aftermarket cable shifter will be allowed if the factory one is broken.
24. Front bumper can be a flat tube MAX size is 4" x 4" x 1/4" , no loading the tube, ends must be open, The bumper can't be no wider than the front tires. 2 chains can be used around the bumper to hold it on the vehicle. The tube can be welded directly to the front frame horns. No additional metal to attach the tube to the vehicle.

